



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11630R1 - 10 Watt LED Direct Wire Downlight; Remote Driver; CCT Selectable; Dimmable; Round; White Finish



GENERAL

Company	SATCO
EA Height	5.51
EA Width	3.74
EA Length	5.31
Mounting Height	3.5
Bulb Included	Integrated
Diameter	4.38
Dimmable Text	Forward or Reverse Phase; 120V only
Material	Aluminum
Fixture Type	Remote Driver LED Downlight
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	<30%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.100A
Mounting Diameter	3.62
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Acrylic
Power Factor	>0.9
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	75W

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	40
Color Temp	Warm White to Natural Light
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	840L
Volts	120v
Watts	10W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Round

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923711916
Case Cube	0.9616
Case Height	12.01
Case Length	12.2
Case Quantity	12
Case UPC	10045923711913
Case Weight	14.33
Case Width	11.34
EA Cube	0.0633
EA Height	5.51
EA Length	5.31
EA Quantity	1
EA Weight	1.12
EA Width	3.74
Pack Type	Box
Web Height	2.17
Web Width	4.38

COMPLIANCE

Air Tight	Yes
CA Prop 65	Lead
Energy Star ID	3798636
FCC Compliant	Yes
IC Rated	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Lawful for sale
Energy Star Certified	Yes
Title 20	Exempt
T24 Compliant	Yes