



S11650 - 9 Watt 2 Foot T5 LED; CCT Selectable; G5 Base; Type B; Ballast Bypass; Single or Double Ended Wiring; White Finish; 120-277 Volt


GENERAL

Company	SATCO
EA Height	0.87
EA Width	0.87
EA Length	21.65
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Plastic
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.7KV
Total Harmonic Distortion	<25%
Tube Guard Use	No
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.075-0.0325A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	24.0
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	14W
Incandescent Equivalent	75W

PACKAGING

UPC	045923116506
Case Cube	0.3834
Case Height	5.24
Case Length	24.13
Case Quantity	25
Case UPC	10045923116503
Case Weight	8.5
Case Width	5.24
EA Cube	0.0095
EA Height	0.87
EA Length	21.65
EA Quantity	1
EA Weight	0.37
EA Width	0.87
Pack Type	Box
Web Length	22.17
Web Width	0.88

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Hours Rated	50000
Beam Angle (degree)	160
Color Temp	Soft White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1100L/1175L/1200L/1250L/1150L
Volts	120V-277V
Watts	9W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	WHITE
Housing Color	White
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.88
MOL	22.17

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes