



S11651 - 12 Watt 3 Foot T5 LED; CCT Selectable; G5 Base; Type B; Ballast Bypass; Single or Double Ended Wiring; White Finish; 120-277 Volt


GENERAL

Company	SATCO
EA Height	0.87
EA Width	0.87
EA Length	33.46
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Plastic
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.7KV
Total Harmonic Distortion	<25%
Tube Guard Use	No
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	1.00-0.043A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	36.0
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	21W
Incandescent Equivalent	60W

PACKAGING

UPC	045923116513
Case Cube	0.5711
Case Height	5.24
Case Length	35.94
Case Quantity	25
Case UPC	10045923116510
Case Weight	10.7
Case Width	5.24
EA Cube	0.0147
EA Height	0.87
EA Length	33.46
EA Quantity	1
EA Weight	0.46
EA Width	0.87
Pack Type	Box
Web Length	33.98
Web Width	0.88

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Hours Rated	50000
Beam Angle (degree)	160
Color Temp	Soft White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1500L/1575L/1600L/1650L/1550L
Volts	120V-277V
Watts	12W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	WHITE
Housing Color	White
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.88
MOL	33.98

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes