



S11653R1 - 12 Watt T5 LED; 35K/4K/5K/65K CCT Selectable; 24 Inch; G5 Base; Type B; PET Coated; Line Voltage Dimmable; 120-347 Volt


GENERAL

| | |
|---------------------------|-----------------------------------|
| Company | SATCO |
| EA Height | 0.75 |
| EA Width | 0.75 |
| EA Length | 22.05 |
| Lamp Ballast Type AB | Type B |
| Dimmable Text | Reverse Phase; 120V only |
| Material | Plastic |
| Fixture Type | Linear |
| Status | Active |
| Surge Protection | Built-in-surge protection - 0.5KV |
| Total Harmonic Distortion | <20% |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.10-0.030A |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lens Material | Glass |
| Nominal Length | 24.0 |
| Operating Position | Universal |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Shatter Proof Type | PET Coated |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Fluor Equiv | 24W |
| Incandescent Equivalent | 60W |

ELECTRICAL

| | |
|---------------------|----------------------------|
| CCT (Kelvin Temp) | 3500K/4000K/5000K/6500K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 180 |
| Color Temp | Neutral White to Daylight |
| CRI | 80+ |
| Dimming Type | 120V only, Phase cut |
| Operating Frequency | 50/60Hz |
| Operating Temp | -20C (-4F) to +45C (+113F) |
| Lumens | 1620L |
| Volts | 120V-347V |
| Watts | 12W |

PHYSICAL

| | |
|-----------|------------------|
| Lamp Base | Miniature Bi Pin |
| Finish | Frost |
| ANSI Base | G5 |
| Lamp Type | T5 |
| MOD Lamps | 0.62 |
| MOL | 22.13 |

ADDITIONAL INFO

| | |
|----------------------------|---------|
| Warranty | 5-Years |
| Rated For Enclosed Fixture | Yes |

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923409981 |
| Case Cube | 0.2911 |
| Case Height | 4.72 |
| Case Length | 24.61 |
| Case Quantity | 25 |
| Case UPC | 10045923409988 |
| Case Weight | 5.05 |
| Case Width | 4.33 |
| EA Cube | 0.0072 |
| EA Height | 0.75 |
| EA Length | 22.05 |
| EA Quantity | 1 |
| EA Weight | 0.19 |
| EA Width | 0.75 |
| Inner Cube | 0.0 |
| Pack Type | Sleeve |
| Web Length | 22.13 |
| Web Width | 0.62 |

COMPLIANCE

| | |
|-----------------|--|
| Dark Sky Rated | No |
| FCC Compliant | Yes |
| IP Rating | IP20 |
| Location Rating | Damp |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cRUus - Recognized Component, cULus - Classified |
| California Ban | Lawful for sale |
| Title 20 | Exempt |
| T24 Compliant | No |