



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11661** - 12 Watt T8 LED; 36 Inch; 30K/35K/40K/50K/65K CCT Selectable; Low Optical Flicker (less than 5%); Medium Bi Pin Base; Type B Ballast Bypass; 120-277 Volt; Frost Finish



**GENERAL**

Company	SATCO
EA Height	1.18
EA Width	1.18
EA Length	36.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Dimmable Text	Reverse Phase; 120V only
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.7KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.130A-0.055A
Has Camera	No
IOT Enabled	No
Nominal Length	36.0
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	25W

**PACKAGING**

UPC	045923116612
Case Cube	0.9661
Case Height	6.69
Case Length	38.39
Case Quantity	25
Case UPC	10045923116619
Case Weight	11.68
Case Width	6.5
EA Cube	0.029
EA Height	1.18
EA Length	36.0
EA Quantity	1
EA Weight	0.4
EA Width	1.18
Pack Type	Sleeve
Web Length	35.24
Web Width	1.0

**COMPLIANCE**

DLC ID	S-L7WLBJ
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	160
Color Temp	Soft White to Daylight
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1450L/1500L/1550L/1550L/1500L
Volts	120V-277V
Watts	12W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	35.24

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

**FEATURES**

Flicker Free	Yes
--------------	-----