



Project / Job Name:

Location:

Fixture Type:

Notes:

S11686 - 11 Watt LED Direct Wire Performer Series
Downlight; Remote Driver; 6 Inch; 27K/3K/35K/4K/5K
CCT Selectable; Round; Flat Face; Black Finish



GENERAL

| | |
|---------------------------|--|
| Company | SATCO |
| EA Height | 6.89 |
| EA Width | 2.2 |
| EA Length | 7.09 |
| Mounting Height | 2.28 |
| Bulb Included | Integrated |
| Center Beam Candle Power | 380 |
| Diameter | 6.77 |
| Dimmable Text | 120V Only |
| Material | Plastic |
| Fixture Type | Remote Driver LED Downlight |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 2.5KV |
| Total Harmonic Distortion | <20% |
| Up Down Installation | Down |
| CCT Selectable | True |
| Wattage Selectable | False |
| Finish Family | Black |
| Additional Info | FT4 cable between driver and lighting head |
| Amps | 0.110A |
| Mounting Diameter | 6.18 |
| Lens Finish | Matte Frosted |
| Lens Material | Polycarbonate (PC) |
| Lensed | True |
| Nominal Length | 6.0 |
| Power Factor | >0.9 |
| SDS Class | LED_Fixture |
| Sloped Ceiling Compatible | Yes |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 75W |

ELECTRICAL

| | |
|---------------------|-------------------------------|
| CCT (Kelvin Temp) | 2700K/3000K/3500K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 110 |
| Color Temp | Warm White to Natural Light |
| CRI | 90+ |
| Dimming Type | Line Voltage |
| Operating Frequency | 60Hz |
| Operating Temp | -20C (-4F) to +40C (+104F) |
| Lumens | 1000L |
| Volts | 120v |
| Watts | 11W |

PHYSICAL

| | |
|---------------|----------------|
| Lamp Base | Integrated |
| Finish | BLACK |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Round |

ADDITIONAL INFO

| | |
|----------|---------|
| Warranty | 5-Years |
|----------|---------|

FEATURES

| | |
|--------------|------|
| Flicker Free | True |
|--------------|------|

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923116865 |
| Case Cube | 0.9183 |
| Case Height | 14.57 |
| Case Length | 14.96 |
| Case Quantity | 12 |
| Case UPC | 10045923116862 |
| Case Weight | 13.01 |
| Case Width | 7.28 |
| EA Cube | 0.0622 |
| EA Height | 6.89 |
| EA Length | 7.09 |
| EA Quantity | 1 |
| EA Weight | 1.0 |
| EA Width | 2.2 |
| Inner Cube | 0.0 |
| Pack Type | Color Box |
| Web Height | 1.18 |
| Web Width | 6.77 |

COMPLIANCE

| | |
|-----------------------|---|
| Air Tight | True |
| CA Regulations | California T24 2016 - 2025 JA8 Listed |
| CA Prop 65 | Lead |
| CA Status | Lawful for sale in California |
| Dark Sky Rated | False |
| Energy Star ID | 4510055 |
| FCC Compliant | True |
| IC Rated | True |
| IP Rating | IP44 |
| Location Rating | Wet |
| NEC Compliance | Clothes Closet Certified - Reg: 410.16 (A)(3) and 410.16 (C)(5) |
| NSF Approved | No |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Certified |
| CA Compliance Text | Lawful for sale |
| Energy Star Certified | Yes |
| Title 20 | No |
| T24 Compliant | True |