



S11697 - 15/11 Watt LED Direct Wire Downlight; 27K/3K/35K/4K/5K; 6-Inch; Dual Dimming; Round; with Integrated Emergency and Test Switch


GENERAL

| | |
|---------------------------|---|
| Company | SATCO |
| EA Height | 6.89 |
| EA Width | 4.72 |
| EA Length | 8.27 |
| Bulb Included | Integrated |
| Diameter | 6.77 |
| Material | Aluminum |
| Fixture Type | Remote Driver LED Downlight |
| Product Notes | Plenum Rated FT6 Cable; Integrated Emergency Driver and Test Switch; Fixture produces 500lm under emergency battery power; Wattage increases by 5W during charging periods. |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 2.5KV |
| Total Harmonic Distortion | <30% |
| Up Down Installation | Down |
| CCT Selectable | Yes |
| Wattage Selectable | Yes |
| Finish Family | White |
| Additional Info | Default Wattage: 15W; Battery Weight: 0.62lbs |
| Amps | 0.092-0.040/0.125-0.054A |
| Integrated Features | Emergency and Test Switch |
| Lens Finish | Matte Frosted |
| Lens Material | Acrylic |
| Lensed | Yes |
| Nominal Length | 6.0 |
| Power Factor | >0.9 |
| SDS Class | Lithium_Ion_Battery |
| Sloped Ceiling Compatible | Yes |
| Indoor Outdoor | Indoor and Outdoor |
| Product Technology | LED |
| Incandescent Equivalent | 85W |

ELECTRICAL

| | |
|---------------------|--|
| CCT (Kelvin Temp) | 2700K/3000K/3500K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 108 |
| Color Temp | Warm White to Natural Light |
| CRI | 90+ |
| Dimming Type | Dual Dimming, Forward or Reverse Phase at 120V/0-10V at 120-277V |
| Operating Frequency | 60Hz |
| Operating Temp | -4F to +104F (-20C to +40C) |
| Lumens | 1350L/1050L |
| Volts | 120V-277V |
| Watts | 15W/11W |

PHYSICAL

| | |
|---------------|----------------|
| Lamp Base | Integrated |
| Finish | WHITE |
| Housing Color | White |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Round |

ADDITIONAL INFO

| | |
|----------|---------|
| Warranty | 5-Years |
|----------|---------|

FEATURES

| | |
|--------------|-----|
| Flicker Free | Yes |
|--------------|-----|

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923116971 |
| Case Cube | 2.1555 |
| Case Height | 14.57 |
| Case Length | 17.32 |
| Case Quantity | 12 |
| Case UPC | 10045923116978 |
| Case Weight | 43.22 |
| Case Width | 14.76 |
| EA Cube | 0.1556 |
| EA Height | 6.89 |
| EA Length | 8.27 |
| EA Quantity | 1 |
| EA Weight | 3.42 |
| EA Width | 4.72 |
| Pack Type | Color Box |
| Web Height | 1.34 |
| Web Width | 6.77 |

COMPLIANCE

| | |
|-----------------------|--------------------|
| ADA Compliant | No |
| Air Tight | Yes |
| CA Prop 65 | Lead |
| Dark Sky Rated | No |
| Energy Star ID | 4517253 |
| FCC Compliant | Yes |
| IC Rated | Yes |
| IP Rating | IP44 |
| Location Rating | Wet |
| NSF Approved | No |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Certified |
| California Ban | Lawful for sale |
| Energy Star Certified | Yes |
| Title 20 | Yes |
| T24 Compliant | Yes |