



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11708 - 7 watt LED Direct Wire Downlight; Gimbaled; 4 inch; 2700K; 120 volt; Dimmable



GENERAL

Company	SATCO
EA Height	5.9
EA Width	3.82
EA Length	5.9
Bulb Included	Integrated
Diameter	5.72
Material	Aluminum / Polycarbonate (PC)
Fixture Type	Direct Wire LED Downlight
Product Notes	Aiming Angle: 30dg
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.058A
Has Camera	No
IOT Enabled	No
Minimum Compartment Size	Height: 4.72 in.
Power Factor	0.95
SDS Class	LED_Fixture
Sloped Ceiling Compatible	Yes
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	45W

ELECTRICAL

CCT (Kelvin Temp)	2700K
Dimmable	Yes-Dimmable
Hours Rated	40000
Beam Angle (degree)	90
Color Temp	Warm White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-4F to +104F (-20C to +40C)
Lumens	490L
Volts	120v
Watts	7W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Round

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923117084
Case Cube	1.1022
Case Height	12.8
Case Length	12.4
Case Quantity	12
Case UPC	10045923117081
Case Weight	9.4
Case Width	12.0
EA Cube	0.077
EA Height	5.9
EA Length	5.9
EA Quantity	1
EA Weight	0.66
EA Width	3.82
Pack Type	Box
Web Height	3.25
Web Width	5.72

COMPLIANCE

Air Tight	Yes
CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	California T24 Listed
UL Application	Ceiling
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24/JA8 Compliant	Yes