



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11741R1 - 9.5 Watt; 4 Foot T8 LED; G13 Base; 3500K; Type A



GENERAL	
Company	SATCO
EA Height	1.1
EA Width	1.1
EA Length	48.0
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required. Direct Replacement- for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Dimmable Text	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Lamp Filament	LED
Material	Glass / Steel
Fixture Type	Linear
Status	Active
Style	Utility
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.079-0.034A
Has Camera	No
IOT Enabled	No
Nominal Length	48.0
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	32W/30W/28W/25W
Incandescent Equivalent	75W

ELECTRICAL	
CCT (Kelvin Temp)	3500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Neutral White
CRI	80+
Dimming Type	Check Ballast MFG for Dimmer Compatibility, Only in Type A mode
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1740L
Volts	Ballast Dependent
Watts	9.5W

PHYSICAL	
Lamp Base	Medium Bi Pin
Finish	Gloss White
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.1
MOL	47.78

ADDITIONAL INFO	
Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING	
UPC	045923402920
Case Cube	0.931
Case Height	5.75
Case Length	48.66
Case Quantity	25
Case UPC	10045923402927
Case Weight	11.78
Case Width	5.75
EA Cube	0.0336
EA Height	1.1
EA Length	48.0
EA Quantity	1
EA Weight	0.43
EA Width	1.1
Pack Type	Sleeve
Web Length	47.78
Web Width	1.1

COMPLIANCE	
DLC ID	S-0K7BB4
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No