Project / Job Name:

Location:

Fixture Type:

Notes:



**S11744** - 14 Watt; 4Ft LED T8; 4000K; 347V Canada Only; G13 Base; Type B Ballast Bypass; Double Ended Wiring

## GENERAL

| | |
|---|---|
| Generational SKU | S21922 |
| Company | SATCO |
| EA Height | 1.1 |
| EA Width | 1.1 |
| EA Length | 48.0 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Plastic |
| Fixture Type | Linear |
| Status | Discontinued |
| Style | Utility |
| Total Harmonic Distortion | 20% |
| Tube Guard Use | Yes |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Additional Info | CANADA ONLY |
| Amps | 0.040A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lens Material | Glass |
| Minimum Compartment Size | Length: 48.43 in. Width: 13.39 in. Height: 1.77 in. |
| Nominal Length | 48.0 |
| Operating Position | Universal |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Fluor Equiv | 32W |
| Incandescent Equivalent | 75W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 4000K |
| Hours Rated | 50000 |
| Beam Angle (degree) | 210 |
| Color Temp | Cool White |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 1800L |
| Volts | 347V |
| Watts | 14W |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Medium Bi Pin |
| Finish | Gloss White |
| Housing Color | White |
| ANSI Base | G13 |
| Lamp Type | T8 |
| MOD Lamps | 1.0 |
| MOL | 47.78 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |

## FEATURES

| | |
|---|---|
| Flicker Free | No |

## PACKAGING

| | |
|---|---|
| UPC | 045923117442 |
| Case Cube | 1.2083 |
| Case Height | 6.0 |
| Case Length | 58.0 |
| Case Quantity | 25 |
| Case UPC | 10045923117449 |
| Case Weight | 11.0 |
| Case Width | 6.0 |
| EA Cube | 0.0336 |
| EA Height | 1.1 |
| EA Length | 48.0 |
| EA Quantity | 1 |
| EA Weight | 0.45 |
| EA Width | 1.1 |
| Pack Type | Sleeve |
| Web Length | 47.78 |
| Web Width | 1.0 |

## COMPLIANCE

| | |
|---|---|
| FCC Compliant | Yes |
| Location Rating | Damp |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cRUus - Recognized Component, cULus - Classified |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026