



S11754 - 30 Watt T8 LED; Recessed Double Contact HO/VHO Base; CCT Selectable; Type B; Ballast Bypass; PET Shatterproof Coated; White Finish; 72 Inches; 120-277 Volt


GENERAL

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	72.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 1KV
Total Harmonic Distortion	<25%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.250-0.108A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	72.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	87W
Incandescent Equivalent	125W

ELECTRICAL

CCT (Kelvin Temp)	4000K/5000K/6500K
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Cool White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	4200L/4300L/4100L
Volts	120V-277V
Watts	30W

PHYSICAL

Lamp Base	Recessed Double Contact HO/VHO
Finish	WHITE
Housing Color	White
ANSI Base	R17d
Lamp Type	T8
MOD Lamps	1.0
MOL	70.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923117541
Case Cube	1.6082
Case Height	4.92
Case Length	71.77
Case Quantity	10
Case UPC	10045923117548
Case Weight	13.33
Case Width	7.87
EA Cube	0.0417
EA Height	1.0
EA Length	72.0
EA Quantity	1
EA Weight	0.86
EA Width	1.0
Inner Cube	0.0
Inner Height	0.0
Inner Length	0.0
Inner Quantity	0
Inner Weight	0.0
Inner Width	0.0
Pack Type	Box
Web Length	70.0
Web Width	1.0

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No