

S11756 - 24/32/40 Wattage Selectable; 8 Foot T8 LED; 30/35/40/50/65K CCT Selectable; 120-277 Volt; FA8 Base


GENERAL

Company	SATCO
EA Height	7.44
EA Width	6.5
EA Length	48.39
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Includes	(20) R17d Base Adapters and (10) Fastening Clips included per case
Status	Discontinued
Style	Utility
Total Harmonic Distortion	20%
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Amps	0.200-0.087/0.267-0.116/0.333-0.144A
Has Camera	No
IOT Enabled	No
Minimum Compartment Size	Length: 96.06 in. Width: 10.63 in. Height: 2.76 in.
Nominal Length	96.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Product Technology	LED
Fluor Equiv	40W/55W/70W
Incandescent Equivalent	100W

PACKAGING

UPC	045923117565
Case Cube	1.3542
Case Height	7.44
Case Length	48.39
Case Quantity	10
Case UPC	10045923117562
Case Weight	12.1
Case Width	6.5
EA Cube	1.3542
EA Height	7.44
EA Length	48.39
EA Quantity	1
EA Weight	12.1
EA Width	6.5
Pack Type	Egg Crate
Web Length	93.75
Web Width	1.0

COMPLIANCE

DLC ID	S-HPN8SY
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Soft White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	3500L/4400L/5500L
Volts	120V-277V
Watts	24W/32W/40W

PHYSICAL

Lamp Base	Single Pin
Finish	WHITE
Housing Color	White
ANSI Base	Fa8
Lamp Type	T8
MOD Lamps	1.0
MOL	93.75

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Must use both sections; Provided support clips may differ from current PI Sheet (SNI394). Please refer to the Instruction Sheet provided in the master carton or downloaded from the website, https://www.satco.com/search/S11756
Rated For Enclosed Fixture	Yes