

Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11758 - 24/32/40 Watt T8 LED; 30K/35K/40K/50K/65K CCT Selectable; 8 Foot; Ballast Bypass; Fa8 Base; 120-277 Volt



GENERAL

Company	SATCO
EA Height	3.86
EA Width	7.56
EA Length	95.87
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	T8
Includes	(1) Set R17d & Fa8 Endcaps
Product Notes	Not for use in fully enclosed vapor tight fixtures
Status	Active
Surge Protection	Built-in surge protection - 1KV
Total Harmonic Distortion	<25%
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Amps	0.200-0.087/0.267-0.116/0.333-0.144A
IOT Enabled	No
Nominal Length	96.0
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Product Technology	LED
Fluor Equiv	59W/86W/96W

ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Soft White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	3500L/4400L/5500L
Volts	120V-277V
Watts	24W/32W/40W

PHYSICAL

Lamp Base	Single Pin
Finish	WHITE
Housing Color	White
ANSI Base	Fa8
Lamp Type	T8
MOD Lamps	1.0
MOL	93.88

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

FEATURES

Flicker Free	No
--------------	----

PACKAGING

UPC	045923117589
Case Cube	1.619
Case Height	3.86
Case Length	95.87
Case Quantity	10
Case UPC	10045923117586
Case Weight	12.13
Case Width	7.56
EA Cube	1.619
EA Height	3.86
EA Length	95.87
EA Quantity	1
EA Weight	12.13
EA Width	7.56
Pack Type	Egg Crate
Web Length	93.88
Web Width	1.0

COMPLIANCE

DLC ID	S-3Y6HM9
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus, cULus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No