



S11760 - 10 Watt T8 LED; CCT Selectable; Medium bi-pin base; 50000 Hours; Type A/B; Ballast Bypass or Direct Replacement; Single or Double Ended Wiring; Glass with PET coating


GENERAL

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	24.0
Lamp Ballast Type AB	Type A/B
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	Linear
Status	Discontinued
Style	Utility
Surge Protection	Built-in-surge protection - 0.7KV
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.083-0.036A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	24.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Product Technology	LED
Fluor Equiv	32W/30W/28W/25W
Incandescent Equivalent	125W

ELECTRICAL

CCT (Kelvin Temp)	3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Neutral White to Natural Light
CRI	80+
Dimming Type	Check Ballast MFG for Dimmer Compatibility, Only in Type A mode
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1425L/1450L/1450L
Volts	120V-277V
Watts	10W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	WHITE
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	23.78

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923117602
Case Cube	0.6696
Case Height	6.7
Case Length	26.57
Case Quantity	25
Case UPC	10045923117609
Case Weight	10.47
Case Width	6.5
EA Cube	0.0139
EA Height	1.0
EA Length	24.0
EA Quantity	1
EA Weight	0.35
EA Width	1.0
Pack Type	Sleeve
Web Length	23.78
Web Width	1.0

COMPLIANCE

DLC ID	S-I8R2WN
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No