



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11764 - 9 Watt; 2 Foot LED; T8; CCT Selectable; Type B Ballast Bypass; G13 Base; 120-277 Volt



GENERAL

Company	SATCO
EA Height	0.94
EA Width	0.94
EA Length	23.78
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	Linear
Status	Active
Style	Utility
Total Harmonic Distortion	<25%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Additional Info	Non CCT Selectable options are S39900-S39903
Amps	0.075-0.032A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	24.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	17W
Incandescent Equivalent	40W

ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Warm White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1150L/1150L/1250L/1250L/1250L
Volts	120V-277V
Watts	9W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	WHITE
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	23.17

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923117640
Case Cube	0.4815
Case Height	5.75
Case Length	24.65
Case Quantity	25
Case UPC	10045923117647
Case Weight	14.4
Case Width	5.87
EA Cube	0.0122
EA Height	0.94
EA Length	23.78
EA Quantity	1
EA Weight	0.44
EA Width	0.94
Pack Type	Sleeve
Web Length	23.17
Web Width	1.0

COMPLIANCE

DLC ID	S-N3X0KC
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No