



**S11767** - 17 Watt; 4 Foot LED; T8; CCT Selectable;  
Type B Ballast Bypass; G13 Base; 120-277 Volt


**GENERAL**

Company	SATCO
EA Height	0.94
EA Width	0.94
EA Length	47.8
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	Linear
Status	Active
Style	Utility
Total Harmonic Distortion	<25%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Additional Info	Non CCT Selectable options are S39904-S39907
Amps	0.142-0.061A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	45W
Incandescent Equivalent	90W

**ELECTRICAL**

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Warm White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	2100L/2100L/2200L/2200L/2200L
Volts	120V-277V
Watts	17W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	WHITE
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	47.17

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923117671
Case Cube	0.9544
Case Height	5.75
Case Length	48.86
Case Quantity	25
Case UPC	10045923117678
Case Weight	14.4
Case Width	5.87
EA Cube	0.0244
EA Height	0.94
EA Length	47.8
EA Quantity	1
EA Weight	0.47
EA Width	0.94
Pack Type	Sleeve
Web Length	47.17
Web Width	1.0

**COMPLIANCE**

DLC ID	S-J4M2XF
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No