



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11829** - 10 Watt; LED Direct Wire Downlight; Edge-lit; 4 inch; CCT Selectable; 120 volt; Dimmable; Square; Remote Driver



**GENERAL**

Company	SATCO
EA Height	5.39
EA Width	2.36
EA Length	6.65
Bulb Included	Integrated
Candle Power	230.0
Dimmable Text	Reverse Phase or Phase Selectable
Material	Aluminum
Fixture Type	Direct Wire LED Downlight
Product Notes	Lumens (L) vary with color temperature (K): 2700K 600L / 3000K 620L / 3500K 650L / 4000K 650L / 5000K 630L
Status	Active
Style	Utility
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Can Size	4 in.
Finish Family	White
Additional Info	Candlepower: 230
Amps	0.083A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Power Factor	>0.9
SDS Class	LED_Lamp
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	45W

**ELECTRICAL**

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	108
Color Temp	Warm to Cool White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	650L
Volts	120v
Watts	10W

**PHYSICAL**

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Square

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	**If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)

**PACKAGING**

UPC	045923118296
Case Cube	0.798
Case Height	6.38
Case Length	15.55
Case Quantity	12
Case UPC	10045923118293
Case Weight	11.68
Case Width	13.9
EA Cube	0.049
EA Height	5.39
EA Length	6.65
EA Quantity	1
EA Weight	0.97
EA Width	2.36
Inner Cube	0.0
Inner Height	0.0
Inner Length	0.0
Inner Quantity	0
Inner Weight	0.0
Inner Width	0.0
Pack Type	Box
Web Height	0.9
Web Length	4.72
Web Width	4.72

**COMPLIANCE**

Air Tight	Yes
CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP20
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	California T24 Listed
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	Yes