



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11843 - 9 Watt; CCT Selectable; LED Direct Wire Downlight; Gimbaled; 4 Inch Square; Remote Driver; Black



GENERAL

Company	SATCO
EA Height	5.08
EA Width	3.07
EA Length	6.34
Bulb Included	Integrated
Material	Aluminum
Fixture Type	Remote Driver LED Downlight
Status	Active
Style	Utility
CCT Selectable	Yes
Wattage Selectable	No
Can Size	4 in.
Finish Family	Black
Additional Info	Candlepower: 750
Amps	0.075A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Plastic
Lensed	Yes
Power Factor	>0.9
SDS Class	LED_Lamp
Sloped Ceiling Compatible	Yes
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	50W

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	36
Color Temp	Warm to Cool White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	650L-750L
Volts	120v
Watts	9W

PHYSICAL

Lamp Base	Integrated
Finish	BLACK
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Square

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	**If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)

PACKAGING

UPC	045923118432
Case Cube	0.8214
Case Height	10.87
Case Length	13.27
Case Quantity	12
Case UPC	10045923118439
Case Weight	12.79
Case Width	9.84
EA Cube	0.0572
EA Height	5.08
EA Length	6.34
EA Quantity	1
EA Weight	1.06
EA Width	3.07
Pack Type	Color Box
Web Height	1.42
Web Length	4.92
Web Width	4.92

COMPLIANCE

Air Tight	Yes
CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP42
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	California T24 Listed
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	Yes