SATCO | NUVO

S11860 - 15 Watt; CCT Selectable; LED Direct Wire Downlight; Gimbaled; 6 Inch Round; Remote Driver; White

GENERAL

Company	SATCO
EA Height	8.19
EA Width	3.94
EA Length	8.11
Bulb Included	Integrated
Diameter	7.48
Dimmable Text	120V only
Material	Aluminum
Fixture Type	Remote Driver LED Downlight
Status	Active
Style	Utility
CCT Selectable	True
Wattage Selectable	False
Can Size	6 in.
Finish Family	White
Amps	0.125A
Has Camera	False
IOT Enabled	False
Lens Finish	Clear
Lens Material	Plastic
Power Factor	>0.9
SDS Class	LED_Lamp
Sloped Ceiling Compatible	Yes
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	75W

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	40
Color Temp	Warm to Cool White
CRI	90+
Dimming Type	Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1280L-1400L
Volts	120v
Watts	15W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Round

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	**If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)

PACKAGING

UPC	045923118609
Case Cube	2.1647
Case Height	17.09
Case Length	16.85
Case Quantity	12
Case UPC	10045923118606
Case Weight	13.92
Case Width	12.99
EA Cube	0.1514
EA Height	8.19
EA Length	8.11
EA Quantity	1
EA Weight	1.16
EA Width	3.94
Inner Cube	0.0
Inner Height	0.0
Inner Length	0.0
Inner Quantity	0
Inner Weight	0.0
Inner Width	0.0
Pack Type	Box
Web Height	2.17
Web Width	7.48

COMPLIANCE

Air Tight	True
CA Regulations	California T24 2016 - 2025 JA8 Listed
CA Prop 65	Lead
CA Status	Lawful for sale in California
FCC Compliant	True
IC Rated	True
IP Rating	IP42
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
CA Compliance Text	California T24 Listed
DLC Approved	False
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	True