



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11862** - 15 Watt; CCT Selectable; LED Direct Wire Downlight; Gimbaled; 6 Inch Round; Remote Driver; Black



**GENERAL**

Company	SATCO
EA Height	8.19
EA Width	3.94
EA Length	8.11
Bulb Included	Integrated
Diameter	7.48
Material	Aluminum
Fixture Type	Remote Driver LED Downlight
Status	Active
Style	Utility
CCT Selectable	Yes
Wattage Selectable	No
Can Size	6 in.
Finish Family	Black
Amps	0.125A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Plastic
Power Factor	>0.9
SDS Class	LED_Lamp
Sloped Ceiling Compatible	Yes
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	75W

**ELECTRICAL**

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	40
Color Temp	Warm to Cool White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1280L-1400L
Volts	120v
Watts	15W

**PHYSICAL**

Lamp Base	Integrated
Finish	BLACK
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Round

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	**If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)

**PACKAGING**

UPC	045923118623
Case Cube	2.1647
Case Height	17.09
Case Length	16.85
Case Quantity	12
Case UPC	10045923118620
Case Weight	13.92
Case Width	12.99
EA Cube	0.1514
EA Height	8.19
EA Length	8.11
EA Quantity	1
EA Weight	1.16
EA Width	3.94
Pack Type	Box
Web Height	2.17
Web Width	7.48

**COMPLIANCE**

Air Tight	Yes
CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP42
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	California T24 Listed
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24/JA8 Compliant	Yes