



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11881 - 15 Watt LED; Fire Rated; 6 Inch Direct Wire Directional Downlight; Round Shape; White Finish; CCT Selectable; Dimmable; 120 Volts



GENERAL

Company	SATCO
EA Height	8.27
EA Width	3.94
EA Length	8.19
Bulb Included	Integrated
Diameter	7.48
Material	Aluminum
Fixture Type	Remote Driver LED Downlight
Product Notes	Rotation Angle 360 degrees; Tilt Angle 80 degrees
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 1.5KV
Total Harmonic Distortion	<30%
CCT Selectable	Yes
Wattage Selectable	No
Can Size	6 in.
Finish Family	White
Additional Info	2HR Fire Rated: Tested to comply with UL 263/ASTM E119/CAN-ULC S101-07
Amps	0.14A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Power Factor	>0.9
SDS Class	LED_Lamp
Sloped Ceiling Compatible	Yes
Indoor Outdoor	Indoor
Product Technology	LED
Fixture Lamp Count	1
Incandescent Equivalent	75W

PACKAGING

UPC	045923118814
Case Cube	2.1874
Case Height	17.32
Case Length	17.32
Case Quantity	12
Case UPC	10045923118811
Case Weight	24.91
Case Width	12.6
EA Cube	0.1544
EA Height	8.27
EA Length	8.19
EA Quantity	1
EA Weight	1.87
EA Width	3.94
Pack Type	Box
Web Height	2.17
Web Width	7.48

COMPLIANCE

Air Tight	Yes
CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	California T24 Listed
UL Application	Covered Ceiling Mount
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24/JA8 Compliant	Yes

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	40
Color Temp	Warm White to Natural Light
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-4F to +104F (-20C to +40C)
Lumens	1280L
Volts	120v
Watts	15W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Round

ADDITIONAL INFO

Warranty	5-Years
----------	---------