



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11905** - 4 Watt T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 400 Lumens; 120-277 Volt; Type B; Ballast Bypass; Double Ended Wiring



**GENERAL**

Company	SATCO
EA Height	0.9
EA Width	0.9
EA Length	12.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	No ballast or external driver required
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Replaces F8T5/CW lamps
Amps	0.033-0.014A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	12.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Product Technology	LED
Fluor Equiv	8W
Incandescent Equivalent	25W

**PACKAGING**

UPC	045923119057
Case Cube	1.186
Case Height	12.6
Case Length	14.76
Case Quantity	100
Case UPC	10045923119054
Case Weight	8.07
Case Width	11.02
EA Cube	0.0056
EA Height	0.9
EA Length	12.0
EA Quantity	1
EA Weight	0.15
EA Width	0.9
Inner Cube	0.1134
Inner Height	2.8
Inner Length	13.2
Inner Quantity	10
Inner UPC	20045923119051
Inner Weight	0.8
Inner Width	5.3
Pack Type	Box
Web Length	11.91
Web Width	0.83

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, ETLus - Sanitation Recognized Component
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	240
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-25C (-13F) to +45C (+113F)
Lumens	400L
Volts	120V-277V
Watts	4W

**PHYSICAL**

Lamp Base	Miniature Bi Pin
Finish	Frost
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.83
MOL	11.91

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring
Rated For Enclosed Fixture	Yes