



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11919** - 12.5 Watt T8 LED; CCT Selectable; G13 base; 50000 Average rated hours; Type B; Ballast Bypass; 2PK



**GENERAL**

Company	SATCO
EA Height	48.0
EA Width	1.5
EA Length	2.75
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.7KV
Total Harmonic Distortion	20%
Tube Guard Use	No
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.104-0.045A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	32W
Incandescent Equivalent	70W

**PACKAGING**

UPC	045923119194
Case Cube	1.4068
Case Height	8.1
Case Length	49.2
Case Quantity	10
Case UPC	10045923119191
Case Weight	7.0
Case Width	6.1
EA Cube	0.1146
EA Height	48.0
EA Length	2.75
EA Quantity	1
EA Weight	0.53
EA Width	1.5
Pack Type	Sleeve
Web Length	47.78
Web Width	1.0

**COMPLIANCE**

DLC ID	PAZ9CLH1
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	4000K/5000K/6500K
Hours Rated	50000
Beam Angle (degree)	220
Color Temp	Cool White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1800L
Volts	120V-277V
Watts	12.5W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	WHITE
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	47.78

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring
Rated For Enclosed Fixture	Yes