



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11921** - 13.5 Watt T8 LED; 3500K; Medium Bi Pin base; 50000 Average rated hours; 1700 Lumens; Dimmable; Type B; Ballast Bypass; Single Ended Wiring



**GENERAL**

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	48.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass; Direct wire 120V line voltage; No ballast or external driver required
Dimmable Text	Reverse Phase or Phase Selectable
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Discontinued
Total Harmonic Distortion	20%
Tube Guard Use	Yes
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.113A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	25W
Incandescent Equivalent	70W

**PACKAGING**

UPC	045923119217
Case Cube	0.9871
Case Height	5.9
Case Length	49.0
Case Quantity	25
Case UPC	10045923119214
Case Weight	13.0
Case Width	5.9
EA Cube	0.0278
EA Height	1.0
EA Length	48.0
EA Quantity	1
EA Weight	0.5
EA Width	1.0
Pack Type	Sleeve
Web Length	48.0
Web Width	1.0

**COMPLIANCE**

DLC ID	PL699Z8XDJKU
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	3500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	220
Color Temp	Neutral White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1700L
Volts	120v
Watts	13.5W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	48.0

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Install only in non-shunted lampholders
Rated For Enclosed Fixture	Yes