



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11924 - 14 Watt T8 LED; Medium bi-pin base; 6500K; 50000 Average rated hours; 1800 Lumens; Type B; Ballast Bypass; Double Ended Wiring



GENERAL

| | |
|-------------------------|---|
| Company | SATCO |
| EA Height | 1.0 |
| EA Width | 1.0 |
| EA Length | 48.0 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required |
| Lamp Filament | LED |
| Material | Glass |
| Fixture Type | Linear |
| Status | Obsolete |
| Tube Guard Use | Yes |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Additional Info | Built-in shock resistant circuit |
| Amps | 0.117-0.051A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lens Material | Glass |
| Lensed | Yes |
| Nominal Length | 48.0 |
| Operating Position | Universal |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Product Technology | LED |
| Fluor Equiv | 25W-32W |
| Incandescent Equivalent | 100W |

ELECTRICAL

| | |
|---------------------|----------------------------|
| CCT (Kelvin Temp) | 6500K |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 210 |
| Color Temp | Daylight |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -20C (-4F) to +45C (+113F) |
| Lumens | 1800L |
| Volts | 120V-277V |
| Watts | 14W |

PHYSICAL

| | |
|-----------|---------------|
| Lamp Base | Medium Bi Pin |
| Finish | Frost |
| ANSI Base | G13 |
| Lamp Type | T8 |
| MOD Lamps | 1.0 |
| MOL | 48.0 |

ADDITIONAL INFO

| | |
|----------------------------|--------------------------------------|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |

PACKAGING

| | |
|----------------|----------------|
| UPC | 045923119248 |
| Case Cube | 0.9871 |
| Case Height | 5.9 |
| Case Length | 49.0 |
| Case Quantity | 25 |
| Case UPC | 10045923119245 |
| Case Weight | 14.4 |
| Case Width | 5.9 |
| EA Cube | 0.0278 |
| EA Height | 1.0 |
| EA Length | 48.0 |
| EA Quantity | 1 |
| EA Weight | 0.5 |
| EA Width | 1.0 |
| Inner Cube | 0.0 |
| Inner Height | 0.0 |
| Inner Length | 0.0 |
| Inner Quantity | 0 |
| Inner Weight | 0.0 |
| Inner Width | 0.0 |
| Pack Type | Sleeve |
| Web Length | 48.0 |
| Web Width | 1.0 |

COMPLIANCE

| | |
|-----------------|--------------------|
| FCC Compliant | Yes |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Classified |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24 Compliant | No |