



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11928 - 10 Watt T8 LED; CCT Selectable; G13 base; 50000 Average rated hours; Type A; Ballast Dependent; 25 PK



GENERAL

Company	SATCO
EA Height	6.7
EA Width	6.5
EA Length	50.0
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required, check compatibility
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Ballast Dependent
Total Harmonic Distortion	20%
Tube Guard Use	No
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.083-0.036A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	30W
Incandescent Equivalent	50W

PACKAGING

UPC	045923119286
Case Cube	1.2601
Case Height	6.7
Case Length	50.0
Case Quantity	25
Case UPC	10045923119283
Case Weight	8.75
Case Width	6.5
EA Cube	1.2601
EA Height	6.7
EA Length	50.0
EA Quantity	1
EA Weight	0.51
EA Width	6.5
Pack Type	Sleeve
Web Length	48.0
Web Width	1.0

COMPLIANCE

DLC ID	PGH9690L
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	220
Color Temp	Cool White to Daylight
CRI	80+
Dimming Type	Check Ballast MFG for Dimmer Compatibility
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1800L
Volts	Ballast Dependent
Watts	10W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	WHITE
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	48.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes