SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:

S11937 - 11 Watt T8 LED; 5000K; 120-277 Volt; Medium Bi Pin base; Type C; External Driver required

GENERAL

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	35.7
Lamp Ballast Type AB	Type C
Ballasting Requirements	Ballast replaced with external driver
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Non-Stock
Style	Utility
Total Harmonic Distortion	20%
Tube Guard Use	Yes
Working Voltage	120-277VAC 39VDC 290mA
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Not for emergency lighting
Amps	0.092-0.040A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	36.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	25W
Incandescent Equivalent	50W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	220
Color Temp	Natural Light
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1600L
Volts	120V-277V
Watts	11W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	None
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	36.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923119378
Case Cube	0.7494
Case Height	5.9
Case Length	37.2
Case Quantity	25
Case UPC	10045923119375
Case Weight	10.2
Case Width	5.9
EA Cube	0.0207
EA Height	1.0
EA Length	35.7
EA Quantity	1
EA Weight	0.34
EA Width	1.0
Pack Type	Sleeve
Web Length	36.0
Web Width	1.0

COMPLIANCE

DLC ID	PLRWRJ8NB39P
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	ETL Sanitation listed (conforms to NSF)
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026