SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:

S11943 - 23 Watt T5 LED; 4000K; 120-277 Volt; Miniature Bi Pin base; Type C; External Driver required



GENERAL

Company	SATCO
EA Height	0.62
EA Width	0.62
EA Length	45.7
Lamp Ballast Type AB	Type C
Ballasting Requirements	Ballast replaced with external driver
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Non-Stock
Style	Utility
Total Harmonic Distortion	20%
Working Voltage	120-277VAC 43VDC 290mA
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Not for emergency lighting
Amps	0.192-0.083A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	54W
Incandescent Equivalent	100W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	220
Color Temp	Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	3400L
Volts	120V-277V
Watts	23W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Frost
Housing Color	None
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.63
MOL	48.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923119439
Case Cube	0.4187
Case Height	3.93
Case Length	46.85
Case Quantity	25
Case UPC	10045923119436
Case Weight	9.43
Case Width	3.93
EA Cube	0.0102
EA Height	0.62
EA Length	45.7
EA Quantity	1
EA Weight	0.33
EA Width	0.62
Pack Type	Sleeve
Web Length	48.0
Web Width	0.63

COMPLIANCE

DLC ID	PLCXVV6NDZC1
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	ETL Sanitation listed (conforms to NSF)
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026