



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11956 - 30 Watt T8 LED Type B Ballast Bypass; G13 Bi-Pin Base; 80 CRI; 5000K



GENERAL

Company	SATCO
EA Height	1.1
EA Width	1.1
EA Length	71.9
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	25%
Tube Guard Use	Yes
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.250-0.108A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	70.0
Operating Position	Universal
Photo Cell	No
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	70W
Incandescent Equivalent	125W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	160
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	4000L
Volts	120V-277V
Watts	30W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	70.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923119569
Case Cube	1.61
Case Height	4.92
Case Length	71.85
Case Quantity	10
Case UPC	10045923119566
Case Weight	5.0
Case Width	7.87
EA Cube	0.0503
EA Height	1.1
EA Length	71.9
EA Quantity	1
EA Weight	0.86
EA Width	1.1
Pack Type	Egg Crate
Web Length	70.0
Web Width	1.0

COMPLIANCE

Dark Sky Rated	No
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified, ETLus - Sanitation Recognized Component
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No