



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11964 - 18 Watt T8 LED; 4 Foot; 4000K; Recessed Double Contact base; 50000 Average rated hours; 2500 Lumens; Type B; Ballast Bypass; Double Ended Wiring



GENERAL

Company	SATCO
EA Height	1.1
EA Width	1.1
EA Length	48.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.7KV
Total Harmonic Distortion	25%
Tube Guard Use	Yes
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.150-0.065A
Has Camera	No
IOT Enabled	No
Lens Finish	White
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	63W
Incandescent Equivalent	90W

PACKAGING

UPC	045923119644
Case Cube	1.089
Case Height	4.92
Case Length	48.6
Case Quantity	10
Case UPC	10045923119641
Case Weight	9.9
Case Width	7.87
EA Cube	0.0336
EA Height	1.1
EA Length	48.0
EA Quantity	1
EA Weight	0.6
EA Width	1.1
Pack Type	Egg Crate
Web Length	46.0
Web Width	1.1

COMPLIANCE

Bug Rating	B0-U0-G0
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	160
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	2500L
Volts	120V-277V
Watts	18W

PHYSICAL

Lamp Base	Recessed Double Contact H0/VH0
Finish	WHITE
Housing Color	White
ANSI Base	R17d
Lamp Type	T8
MOD Lamps	1.1
MOL	46.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes