

Project / Job Name:

Location:

Fixture Type:

Notes:



S11978 - 10.5 Watt T8 LED; 4Ft; 4000K; Medium Bi Pin base; 70000 Average rated hours; 1650 Lumens; Type B; Ballast Bypass; Single Ended-Double Ended; Plastic



GENERAL

Company	SATCO
EA Height	1.1
EA Width	1.1
EA Length	48.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Plastic
Fixture Type	Linear
Status	Active
Style	Utility
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.088-0.038A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Plastic
Nominal Length	48.0
Operating Position	Universal
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	25W/28W/32W
Incandescent Equivalent	50W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Hours Rated	70000
Beam Angle (degree)	180
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Lumens	1650L
Volts	120V-277V
Watts	10.5W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	47.78

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.

PACKAGING

UPC	045923119781
Case Cube	1.2582
Case Height	6.69
Case Length	50.0
Case Quantity	25
Case UPC	10045923119788
Case Weight	14.4
Case Width	6.5
EA Cube	0.0336
EA Height	1.1
EA Length	48.0
EA Quantity	1
EA Weight	0.44
EA Width	1.1
Pack Type	Sleeve
Web Length	47.78
Web Width	1.0

COMPLIANCE

DLC ID	S-PE2TIM
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No