



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11983 - 9 Watt; 24 Inch; T8 LED; 5000K; Medium Bi Pin base; 82 CRI; 50000 Average rated hours; Type B Ballast Bypass; 1150 Lumens; Assembled in the USA



GENERAL

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	24.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	Linear
Product Notes	Compatible with S8000 and S8002 LED EM Driver
Status	Discontinued
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.075-0.032A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	24.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	17W
Incandescent Equivalent	40W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1150L
Volts	120V-277V
Watts	9W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	23.78

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923119835
Case Cube	0.5515
Case Height	6.3
Case Length	24.8
Case Quantity	25
Case UPC	10045923119832
Case Weight	6.88
Case Width	6.1
EA Cube	0.0139
EA Height	1.0
EA Length	24.0
EA Quantity	1
EA Weight	0.28
EA Width	1.0
Inner Cube	0.0
Inner Height	0.0
Inner Length	0.0
Inner Quantity	0
Inner Weight	0.0
Inner Width	0.0
Pack Type	Sleeve
Web Length	23.78
Web Width	1.0

COMPLIANCE

Dark Sky Rated	No
DLC ID	PLL16UMVG8VL
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt