



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11992** - 14 Watt; 48 Inch; T8 LED; 3000K; Medium Bi Pin base; 82 CRI; 50000 Average rated hours; Type B Ballast Bypass; 1700 Lumens; Assembled in the USA



**GENERAL**

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	48.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	Linear
Product Notes	Compatible with S8000 and S8002 LED EM Driver
Status	Discontinued
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.117-0.051A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	30W
Incandescent Equivalent	75W

**ELECTRICAL**

CCT (Kelvin Temp)	3000K
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Warm White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1700L
Volts	120V-277V
Watts	14W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	47.78

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923119927
Case Cube	1.0853
Case Height	6.3
Case Length	48.8
Case Quantity	25
Case UPC	10045923119924
Case Weight	14.4
Case Width	6.1
EA Cube	0.0278
EA Height	1.0
EA Length	48.0
EA Quantity	1
EA Weight	0.58
EA Width	1.0
Pack Type	Sleeve
Web Length	47.78
Web Width	1.0

**COMPLIANCE**

Dark Sky Rated	No
DLC ID	PLFJY8MPT5PV
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt