



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S12138 - 4.5 Watt Mini LED; Bayonet Single Contact Base; 3000K; Clear Finish; 12 Volt**



### GENERAL

|                           |  |
|---------------------------|--|
| Company                   | SATCO  |
| EA Height                 | 4.84   |
| EA Width                  | 0.73   |
| EA Length                 | 3.27   |
| Candle Power              | 35.0   |
| Lamp Filament             | LED  |
| Material                  | Ceramic / Polycarbonate (PC)                                 |
| Fixture Type              | Miniature  |
| Status                    | Active   |
| Style                     | Utility  |
| Surge Protection          | Built-in surge protection - 1.5KV                            |
| Total Harmonic Distortion | 70%  |
| CCT Selectable            | No   |
| Wattage Selectable        | No   |
| Finish Family             | Clear  |
| Additional Info           | Housing Material: Ceramic; Lens Material: Polycarbonate (PC) |
| Amps                      | 0.490A   |
| Has Camera                | No   |
| IOT Enabled               | No   |
| SDS Class                 | LED_Lamp   |
| Indoor Outdoor            | Indoor   |
| Product Technology        | LED  |
| Incandescent Equivalent   | 40W  |

### ELECTRICAL

|                     |   |
|---------------------|---|
| CCT (Kelvin Temp)   | 3000K   |
| Dimmable            | Yes-Dimmable  |
| Hours Rated         | 25000   |
| Beam Angle (degree) | 300   |
| Color Temp          | Soft White  |
| CRI                 | 80+   |
| Dimming Type        | Check the transformer/driver MFG for dimmer compatibility |
| Operating Frequency | 60Hz  |
| Operating Temp      | -4F to +104F (-20C to +40C)                               |
| Lumens              | 430L  |
| Volts               | 12V   |
| Watts               | 4.5W  |

### PHYSICAL

|               |                        |
|---------------|------------------------|
| Lamp Base     | Bayonet Single Contact |
| Finish        | Clear                  |
| Housing Color | White                  |
| ANSI Base     | BA15s                  |
| Lamp Type     | T6                     |
| MOD Lamps     | 0.67                   |
| MOL           | 2.09                   |

### ADDITIONAL INFO

|                            |         |
|----------------------------|---------|
| Warranty                   | 5-Years |
| Rated For Enclosed Fixture | Yes     |

### PACKAGING

|                |                |
|----------------|----------------|
| UPC            | 045923121388   |
| Case Cube      | 0.666          |
| Case Height    | 12.13          |
| Case Length    | 10.04          |
| Case Quantity  | 48             |
| Case UPC       | 10045923121385 |
| Case Weight    | 4.63           |
| Case Width     | 9.45           |
| EA Cube        | 0.0067         |
| EA Height      | 4.84           |
| EA Length      | 3.27           |
| EA Quantity    | 1              |
| EA Weight      | 0.07           |
| EA Width       | 0.73           |
| Inner Cube     | 0.1342         |
| Inner Height   | 5.63           |
| Inner Length   | 8.86           |
| Inner Quantity | 12             |
| Inner UPC      | 20045923121382 |
| Inner Weight   | 0.96           |
| Inner Width    | 4.65           |
| Pack Type      | Carded         |
| Web Length     | 2.09           |
| Web Width      | 0.67           |

### COMPLIANCE

|                   |                                   |
|-------------------|-----------------------------------|
| FCC Compliant     | Yes                               |
| Location Rating   | Damp                              |
| ROHS Compliant    | Yes                               |
| Safety Listing    | cULus - Certified, cULus - Listed |
| California Ban    | Lawful for sale                   |
| DLC Approved      | No                                |
| Title 20          | Exempt                            |
| T24/JA8 Compliant | No                                |