



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S12260** - 3.5 Watt; R14 LED; Intermediate Base; 3000K CCT; Frost Finish; 120 Volt



### GENERAL

Company	SATCO
EA Height	6.5
EA Width	1.78
EA Length	4.06
Candle Power	90.0
Center Beam Candle Power	90
Lamp Filament	LED
Material	Plastic
Fixture Type	Miniature
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2.5KV
Total Harmonic Distortion	26%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.029A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Polycarbonate (PC)
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	40W

### ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	110
Color Temp	Soft White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	300L
Volts	120v
Watts	3.5W

### PHYSICAL

Lamp Base	Intermediate
Finish	Frost
Housing Color	White
ANSI Base	E17
Lamp Type	R14
MOD Lamps	1.78
MOL	2.56

### ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

### PACKAGING

UPC	045923122606
Case Cube	0.5281
Case Height	7.28
Case Length	12.99
Case Quantity	12
Case UPC	10045923122603
Case Weight	1.08
Case Width	9.65
EA Cube	0.0272
EA Height	6.5
EA Length	4.06
EA Quantity	1
EA Weight	0.08
EA Width	1.78
Pack Type	Carded
Web Length	2.56
Web Width	1.78

### COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	Yes