



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12261 - 3.5 Watt; R14 LED; Intermediate Base; 5000K CCT; Frost Finish; 120 Volt



GENERAL

Company	SATCO
EA Height	6.5
EA Width	1.78
EA Length	4.06
Candle Power	90.0
Center Beam Candle Power	90
Dimmable Text	120V only
Lamp Filament	LED
Material	Plastic
Status	Discontinued
Style	Utility
Surge Protection	Built-in surge protection - 2.5KV
Total Harmonic Distortion	26%
CCT Selectable	False
Wattage Selectable	False
Finish Family	White
Amps	0.029A
Has Camera	False
IOT Enabled	False
Lens Finish	Frost
Lens Material	Polycarbonate (PC)
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	40W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	110
Color Temp	Natural Light
CRI	90+
Dimming Type	Forward Phase or Reverse Phase or Phase Selectable or Triac
Operating Frequency	60Hz
Operating Temp	-25C (-13F) to +45C (+113F)
Lumens	300L
Volts	120v
Watts	3.5W

PHYSICAL

Lamp Base	Intermediate
Finish	Frost
Housing Color	White
ANSI Base	E17
Lamp Type	R14
MOD Lamps	1.78
MOL	2.56

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	True

PACKAGING

UPC	045923122613
Case Cube	0.5281
Case Height	7.28
Case Length	12.99
Case Quantity	12
Case UPC	10045923122610
Case Weight	1.08
Case Width	9.65
EA Cube	0.0272
EA Height	6.5
EA Length	4.06
EA Quantity	1
EA Weight	0.08
EA Width	1.78
Inner Cube	0.0
Pack Type	Carded
Web Length	2.56
Web Width	1.78

COMPLIANCE

CA Regulations	T20 Listed
CA Status	Lawful for sale in California
FCC Compliant	True
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
CA Compliance Text	Lawful for sale
DLC Approved	False
Title 20	Yes
T24 Compliant	False