



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12315 - 4.5 Watt T6 LED; Clear Finish; Bi Pin G4 Base; 5000K; 12 Volt



| GENERAL | |
|---------------------------|---|
| Company | SATCO |
| EA Height | 2.95 |
| EA Width | 1.5 |
| EA Length | 1.5 |
| Candle Power | 35.0 |
| Center Beam Candle Power | 35 |
| Dimmable Text | Check the transformer/driver MFG for dimmer compatibility |
| Lamp Filament | LED |
| Material | Ceramic / Polycarbonate (PC) |
| Fixture Type | Tubular |
| Status | Discontinued |
| Style | Utility |
| Surge Protection | Built-in surge protection - 1.5KV |
| Total Harmonic Distortion | 70% |
| CCT Selectable | False |
| Wattage Selectable | False |
| Finish Family | Clear |
| Amps | 0.490A |
| Has Camera | False |
| IOT Enabled | False |
| Lens Material | Polycarbonate (PC) |
| Power Factor | 0.7 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 35W |

| ELECTRICAL | |
|---------------------|----------------------------|
| CCT (Kelvin Temp) | 5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 25000 |
| Beam Angle (degree) | 300 |
| Color Temp | Natural Light |
| CRI | 80+ |
| Dimming Type | Phase cut |
| Operating Frequency | 60Hz |
| Operating Temp | -20C (-4F) to +40C (+104F) |
| Lumens | 430L |
| Volts | 12V |
| Watts | 4.5W |

| PHYSICAL | |
|---------------|-----------|
| Lamp Base | Bi Pin G4 |
| Finish | Clear |
| Housing Color | White |
| ANSI Base | G4 |
| Lamp Type | T6 |
| MOD Lamps | 0.73 |
| MOL | 1.81 |

| ADDITIONAL INFO | |
|----------------------------|--------------------------------------|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | True |

| FEATURES | |
|--------------|-------|
| Flicker Free | False |

| PACKAGING | |
|----------------|----------------|
| UPC | 045923123153 |
| Case Cube | 1.1904 |
| Case Height | 13.62 |
| Case Length | 17.44 |
| Case Quantity | 200 |
| Case UPC | 10045923123150 |
| Case Weight | 9.1 |
| Case Width | 8.66 |
| EA Cube | 0.0038 |
| EA Height | 2.95 |
| EA Length | 1.5 |
| EA Quantity | 1 |
| EA Weight | 0.035 |
| EA Width | 1.5 |
| Inner Cube | 0.1004 |
| Inner Height | 6.42 |
| Inner Length | 8.07 |
| Inner Quantity | 20 |
| Inner UPC | 20045923123157 |
| Inner Weight | 0.82 |
| Inner Width | 3.35 |
| Pack Type | Box |
| Web Length | 1.81 |
| Web Width | 0.73 |

| COMPLIANCE | |
|--------------------|-----------------------------------|
| CA Regulations | Exempt - Base Not Regulated |
| CA Status | Lawful for sale in California |
| FCC Compliant | True |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Listed |
| CA Compliance Text | Lawful for sale |
| DLC Approved | False |
| Title 20 | Exempt |
| T24 Compliant | False |