



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12330 - 2 Watt T4 LED; Frost Finish; G9 Base; 3000K; 120 Volt



GENERAL	
Company	SATCO
EA Height	2.95
EA Width	1.5
EA Length	1.5
Candle Power	20.0
Center Beam Candle Power	20
Dimmable Text	Forward Phase
Lamp Filament	LED
Material	Ceramic / Glass
Fixture Type	Tubular
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 1.5KV
Total Harmonic Distortion	70%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.020A
Has Camera	No
IOT Enabled	No
Lens Material	Glass
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	15W

ELECTRICAL	
CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	300
Color Temp	Soft White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +40C (+104F)
Lumens	180L
Volts	120v
Watts	2W

PHYSICAL	
Lamp Base	G9 Double Loop
Finish	Frost
Housing Color	White
ANSI Base	G9
Lamp Type	T4
MOD Lamps	0.51
MOL	1.77

ADDITIONAL INFO	
Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING	
UPC	045923123306
Case Cube	1.1904
Case Height	13.62
Case Length	17.44
Case Quantity	200
Case UPC	10045923123303
Case Weight	8.22
Case Width	8.66
EA Cube	0.0038
EA Height	2.95
EA Length	1.5
EA Quantity	1
EA Weight	0.031
EA Width	1.5
Inner Cube	0.1004
Inner Height	6.42
Inner Length	8.07
Inner Quantity	20
Inner UPC	20045923123300
Inner Weight	0.73
Inner Width	3.35
Pack Type	Box
Web Length	1.77
Web Width	0.51

COMPLIANCE	
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No