



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12353 - 5 Watt T6 LED; Frost Finish; DC Base; 5000K; 120 Volt



GENERAL

Company	SATCO
EA Height	2.95
EA Width	1.5
EA Length	1.5
Candle Power	38.0
Center Beam Candle Power	38
Lamp Filament	LED
Material	Ceramic / Polycarbonate (PC)
Fixture Type	Tubular
Status	Discontinued
Style	Utility
Surge Protection	Built-in surge protection - 1.5KV
Total Harmonic Distortion	70%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.046A
Has Camera	No
IOT Enabled	No
Lens Material	Polycarbonate (PC)
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	40W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	300
Color Temp	Natural Light
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-4F to +104F (-20C to +40C)
Lumens	500L
Volts	120v
Watts	5W

PHYSICAL

Lamp Base	Bayonet Double Contact
Finish	Frost
Housing Color	White
ANSI Base	BA15d
Lamp Type	T6
MOD Lamps	0.75
MOL	2.24

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923123535
Case Cube	1.1904
Case Height	13.62
Case Length	17.44
Case Quantity	200
Case UPC	10045923123532
Case Weight	14.83
Case Width	8.66
EA Cube	0.0038
EA Height	2.95
EA Length	1.5
EA Quantity	1
EA Weight	0.064
EA Width	1.5
Inner Cube	0.1004
Inner Height	6.42
Inner Length	8.07
Inner Quantity	20
Inner UPC	20045923123539
Inner Weight	1.4
Inner Width	3.35
Pack Type	Box
Web Length	2.24
Web Width	0.75

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No