Project / Job Name:

Location:

Fixture Type:

Notes:



**S12362** - 5.5 Watt MR16 LED Spotlight; 3500K CCT; GU5.3 Base; 12 Volt

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 2.36 |
| EA Width | 1.89 |
| EA Length | 1.89 |
| Lamp Filament | LED |
| Material | Glass |
| Fixture Type | Miniature |
| Status | Discontinued |
| Style | Contemporary |
| Surge Protection | Built-in-surge protection - 0.5KV |
| Total Harmonic Distortion | 50% |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | Clear |
| Amps | 0.458A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) |
| Lensed | Yes |
| Power Factor | 0.7 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 50W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3500K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 25000 |
| Beam Angle (degree) | 15 |
| Color Temp | Neutral White |
| CRI | 90+ |
| Dimming Type | Check the transformer/driver MFG for dimmer compatibility |
| Operating Frequency | 60Hz |
| Operating Temp | -13F to +113F (-25C to +45C) |
| Lumens | 500L |
| Volts | 12V |
| Watts | 5.5W |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Bi Pin GU5.3 |
| Finish | Clear |
| Housing Color | None |
| ANSI Base | GU5.3 |
| Lamp Type | MR16 |
| MOD Lamps | 1.97 |
| MOL | 1.73 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |
| Rated For Enclosed Fixture | Yes |

## PACKAGING

| | |
|---|---|
| UPC | 045923123627 |
| Case Cube | 0.3622 |
| Case Height | 5.98 |
| Case Length | 12.2 |
| Case Quantity | 48 |
| Case UPC | 10045923123624 |
| Case Weight | 6.0 |
| Case Width | 8.58 |
| EA Cube | 0.0049 |
| EA Height | 2.36 |
| EA Length | 1.89 |
| EA Quantity | 1 |
| EA Weight | 0.11 |
| EA Width | 1.89 |
| Inner Cube | 0.0741 |
| Inner Height | 2.68 |
| Inner Length | 11.89 |
| Inner Quantity | 12 |
| Inner UPC | 20045923123621 |
| Inner Weight | 1.4 |
| Inner Width | 4.02 |
| Pack Type | Box |
| Web Length | 1.73 |
| Web Width | 1.97 |

## COMPLIANCE

| | |
|---|---|
| FCC Compliant | Yes |
| IP Rating | IP20 |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Listed |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Yes |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026