



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12366 - 5.5 Watt MR16 LED Floodlight; 3000K CCT; GU5.3 Base; 12 Volt



GENERAL

Company	SATCO
EA Height	2.36
EA Width	1.89
EA Length	1.89
Dimmable Text	Check the transformer/driver MFG for dimmer compatibility
Lamp Filament	LED
Material	Glass
Fixture Type	Flood Light
Status	Active
Style	Contemporary
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	50%
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Amps	0.458A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Lensed	Yes
Power Factor	0.7
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	50W

ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	36
Color Temp	Soft White
CRI	90+
Dimming Type	Check the transformer/driver MFG for dimmer compatibility
Operating Frequency	60Hz
Operating Temp	-25C (-13F) to +45C (+113F)
Lumens	500L
Volts	12V
Watts	5.5W

PHYSICAL

Lamp Base	Bi Pin GU5.3
Finish	Clear
Housing Color	None
ANSI Base	GU5.3
Lamp Type	MR16
MOD Lamps	1.97
MOL	1.73

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923123665
Case Cube	0.3622
Case Height	5.98
Case Length	12.2
Case Quantity	48
Case UPC	10045923123662
Case Weight	6.0
Case Width	8.58
EA Cube	0.0049
EA Height	2.36
EA Length	1.89
EA Quantity	1
EA Weight	0.11
EA Width	1.89
Inner Cube	0.0741
Inner Height	2.68
Inner Length	11.89
Inner Quantity	12
Inner UPC	20045923123669
Inner Weight	1.4
Inner Width	4.02
Pack Type	Box
Web Length	1.73
Web Width	1.97

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24 Compliant	No