



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12600 - 6 Watt LED Downlight Retrofit; 4 Inch; CCT Selectable; Round; White Finish



GENERAL

Company	SATCO
EA Height	5.43
EA Width	2.28
EA Length	5.43
Mounting Height	3.94
Bulb Included	Integrated
Diameter	5.3
Dimmable Text	Forward or Reverse Phase; 120V only
Material	Plastic
Fixture Type	Downlight Retrofit
Status	Active
Style	Utility
Surge Protection	Built-in-surge protection - 0.5KV
CCT Selectable	Yes
Wattage Selectable	No
Can Size	4 in.
Finish Family	White
Amps	0.065A
Mounting Diameter	4.06
Has Camera	No
IOT Enabled	No
Lens Finish	Matte Frosted
Lens Material	Plastic
Lensed	Yes
Power Factor	>0.9
SDS Class	LED Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	50W

PACKAGING

UPC	045923126000
Case Cube	0.5535
Case Height	5.83
Case Length	14.57
Case Quantity	12
Case UPC	10045923126007
Case Weight	4.87
Case Width	11.26
EA Cube	0.0389
EA Height	5.43
EA Length	5.43
EA Quantity	1
EA Weight	0.34
EA Width	2.28
Pack Type	Box
Web Height	1.48
Web Width	5.3

COMPLIANCE

Air Tight	Yes
CA Prop 65	Lead
Energy Star ID	3893938
FCC Compliant	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cETLus - Classified
California Ban	Lawful for sale
Energy Star Certified	Yes
Title 20	Yes
T24 Compliant	Yes

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	90
Color Temp	Warm White to Natural Light
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +40C (+104F)
Lumens	600L
Volts	120v
Watts	6.5W

PHYSICAL

Lamp Base	Medium Adapter
Finish	WHITE
ANSI Base	E26 Adapter
Lamp Type	Integrated LED
Fixture Shape	Round

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Default CCT setting is 3000K