



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13112 - 80 Watt - LED HID Replacement; 4000K; Mogul extended base; Type B Ballast Bypass; 120-277 Volt



GENERAL

Company	SATCO
EA Height	10.43
EA Width	7.48
EA Length	7.48
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Candle Power	3000.0
Center Beam Candle Power	3000
Lamp Filament	LED
Material	Plastic
Fixture Type	Hi-Bay
Status	Discontinued
Style	Contemporary
Surge Protection	Built-in surge protection - 6KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.667-0.2889A
Has Camera	No
IOT Enabled	No
Lens Finish	Translucent White
Lensed	Yes
Minimum Compartment Size	Length: 13.5 in. Width: 13.5 in. Height: 12 in.
Operating Position	Universal
Power Factor	0.98/0.92
SDS Class	LED_Lamp
Product Technology	LED
Incandescent Equivalent	400W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	115
Color Temp	Cool White
CRI	80+
Operating Frequency	50-60Hz
Operating Temp	-40F to +140F (-40C to +60C)
HID Equivalent	250W
Lumens	10000L
Volts	120V-277V
Watts	80W

PHYSICAL

Lamp Base	Mogul Extended
Finish	Translucent White
Housing Color	White
ANSI Base	EX39
Lamp Type	HB60
MOD Lamps	7.48
MOL	10.12

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923131127
Case Cube	1.6909
Case Height	11.69
Case Length	15.87
Case Quantity	4
Case UPC	10045923131124
Case Weight	10.25
Case Width	15.75
EA Cube	0.3377
EA Height	10.43
EA Length	7.48
EA Quantity	1
EA Weight	2.16
EA Width	7.48
Pack Type	Box
Web Length	10.12
Web Width	7.48

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No