



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13114 - 130 Watt - LED HID Replacement; 4000K; Mogul extended base; Type B Ballast Bypass; 120-277 Volt



GENERAL

Company	SATCO
EA Height	12.72
EA Width	9.65
EA Length	9.65
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Candle Power	5000.0
Center Beam Candle Power	5000
Lamp Filament	LED
Material	Plastic
Fixture Type	Hi-Bay
Status	Discontinued
Style	Contemporary
Surge Protection	Built-in surge protection - 6KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	1.083-0.469A
Has Camera	No
IOT Enabled	No
Lens Finish	Translucent White
Lensed	Yes
Minimum Compartment Size	Length: 16.5 in. Width: 16.5 in. Height: 13 in.
Operating Position	Universal
Power Factor	0.99/0.95
SDS Class	LED_Lamp
Product Technology	LED
Incandescent Equivalent	2000W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	115
Color Temp	Cool White
CRI	80+
Operating Frequency	50-60Hz
Operating Temp	-40F to +140F (-40C to +60C)
HID Equivalent	400W
Lumens	16300L
Volts	120V-277V
Watts	130W

PHYSICAL

Lamp Base	Mogul Extended
Finish	Translucent White
Housing Color	White
ANSI Base	EX39
Lamp Type	HB77
MOD Lamps	9.65
MOL	12.4

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923131141
Case Cube	3.2815
Case Height	13.98
Case Length	20.2
Case Quantity	4
Case UPC	10045923131148
Case Weight	16.64
Case Width	20.08
EA Cube	0.6855
EA Height	12.72
EA Length	9.65
EA Quantity	1
EA Weight	3.62
EA Width	9.65
Pack Type	Box
Web Length	12.4
Web Width	9.65

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No