



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13148 - 40/30/20 Watt LED HID Replacement; 3K/4K/5K CCT Selectable; Ballast Bypass; Medium Base; 120-277 Range Voltage



GENERAL

| | |
|---------------------------|--------------------------------------|
| Company | SATCO |
| EA Height | 7.05 |
| EA Width | 6.69 |
| EA Length | 6.69 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Aluminum |
| Fixture Type | LED HID |
| Status | Active |
| Surge Protection | Built-in surge protection - 4KV |
| Total Harmonic Distortion | <20% |
| CCT Selectable | Yes |
| Wattage Selectable | Yes |
| Finish Family | Clear |
| Amps | 0.333-0.144/0.250-0.108/0.167-0.072A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Translucent |
| Lens Material | Polycarbonate (PC) |
| Lensed | Yes |
| Operating Position | Base Down |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor and Outdoor |
| Product Technology | LED |

ELECTRICAL

| | |
|---------------------|---|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 120 |
| Color Temp | Soft White to Natural Light |
| CRI | 80+ |
| Dimming Type | Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls., Step Dimming |
| Operating Frequency | 50/60Hz |
| Operating Temp | -13F to +122F (-25C to +50C) |
| HID Equivalent | 150W-175W |
| Lumens | 5800L-6400L/4350L-4800L/2900L-3200L |
| Volts | 120V-277V |
| Watts | 40W/30W/20W |

PHYSICAL

| | |
|---------------|---------|
| Lamp Base | Medium |
| Finish | Clear |
| Housing Color | White |
| ANSI Base | E26 |
| Lamp Type | Corncob |
| MOD Lamps | 5.69 |
| MOL | 5.68 |

ADDITIONAL INFO

| | |
|----------------------------|---------|
| Warranty | 5-Years |
| Rated For Enclosed Fixture | Yes |

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923131486 |
| Case Cube | 2.5669 |
| Case Height | 15.35 |
| Case Length | 20.67 |
| Case Quantity | 12 |
| Case UPC | 10045923131483 |
| Case Weight | 28.66 |
| Case Width | 13.98 |
| EA Cube | 0.1826 |
| EA Height | 7.05 |
| EA Length | 6.69 |
| EA Quantity | 1 |
| EA Weight | 1.95 |
| EA Width | 6.69 |
| Pack Type | Box |
| Web Length | 5.68 |
| Web Width | 5.69 |

COMPLIANCE

| | |
|-------------------|-----------------|
| FCC Compliant | Yes |
| IP Rating | IP65 |
| Location Rating | Wet |
| ROHS Compliant | Yes |
| Safety Listing | cULus |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |