



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13154 - 152 Watt - LED HID Replacement; 4K; EX39; Type B Ballast Bypass; 120-277 Volt



GENERAL

Company	SATCO
EA Height	9.25
EA Width	9.45
EA Length	11.02
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Plastic
Fixture Type	Hi-Bay Flood
Status	Discontinued
Style	Contemporary
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	1.267-0.549A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Glass
Lensed	Yes
Minimum Compartment Size	Diameter: 19.69 in. Height: 19.69 in.
Operating Position	Base Up
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	250W
Incandescent Equivalent	1000W

PACKAGING

UPC	045923131547
Case Cube	2.4649
Case Height	9.84
Case Length	22.44
Case Quantity	4
Case UPC	10045923131544
Case Weight	21.0
Case Width	19.29
EA Cube	0.5575
EA Height	9.25
EA Length	11.02
EA Quantity	1
EA Weight	5.25
EA Width	9.45
Pack Type	Box
Web Length	9.33
Web Width	7.91

COMPLIANCE

DLC ID	PNUQ2VIP
FCC Compliant	Yes
IP Rating	IP40
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	4000K
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-40F to +140F (-40C to +60C)
HID Equivalent	750W
Lumens	25000L
Volts	120V-277V
Watts	152W

PHYSICAL

Lamp Base	Mogul Extended
Finish	WHITE
Housing Color	White
ANSI Base	EX39
Lamp Type	HB64
MOD Lamps	7.91
MOL	9.33

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures. Vertical Only with base up
Rated For Enclosed Fixture	Yes