



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13160 - 20 Watt; A-Plus 23; LED; CCT Selectable
3K/4K/5K; Medium base; Type B; Ballast Bypass;
100-277 Volt; ColorQuick Technology



GENERAL

Company	SATCO
EA Height	5.7
EA Width	2.99
EA Length	2.99
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Aluminum
Fixture Type	Type A
Product Notes	Lumen/Watt/CCT Ratio Chart in Documents.
Status	Active
Style	Contemporary
Surge Protection	Built-in surge protection - 1KV
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.200-0.0722A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Polycarbonate (PC)
Minimum Compartment Size	Length: 6 in. Width: 6 in. Height: 8.5 in.
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	55W
Incandescent Equivalent	150W

PACKAGING

UPC	045923131608
Case Cube	0.877
Case Height	12.4
Case Length	12.6
Case Quantity	24
Case UPC	10045923131605
Case Weight	15.8
Case Width	9.7
EA Cube	0.0295
EA Height	5.7
EA Length	2.99
EA Quantity	1
EA Weight	0.63
EA Width	2.99
Pack Type	Box
Web Length	5.12
Web Width	2.83

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP64
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	280
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls., Step Dimming
Operating Frequency	50/60Hz
Operating Temp	-30F to +113F (-22C to +45C)
HID Equivalent	70W-100W
Lumens	2400L/2700L/2600L
Volts	120V-277V
Watts	20W

PHYSICAL

Lamp Base	Medium
Finish	WHITE
Housing Color	White
ANSI Base	E26
Lamp Type	AP23
MOD Lamps	2.83
MOL	5.12

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes