



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13161 - 25 Watt; A-Plus 23; LED; CCT Selectable
3K/4K/5K; Medium base; Type B; Ballast Bypass;
100-277 Volt; ColorQuick Technology



GENERAL

| | |
|--------------------------|---|
| Company | SATCO |
| EA Height | 5.7 |
| EA Width | 2.99 |
| EA Length | 2.99 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Dimmable Text | Step Dimming; Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. |
| Lamp Filament | LED |
| Material | Aluminum |
| Fixture Type | Type A |
| Product Notes | Lumen/Watt/CCT Ratio Chart in Documents. |
| Status | Active |
| Style | Contemporary |
| Surge Protection | Built-in surge protection - 1KV |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.250-0.090A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lens Material | Polycarbonate (PC) |
| Minimum Compartment Size | Length: 6 in. Width: 6 in. Height: 8.5 in. |
| Operating Position | Universal |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Fluor Equiv | 65W |
| Incandescent Equivalent | 200W |

ELECTRICAL

| | |
|---------------------|---|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 280 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Dimming Type | Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls., Step Dimming |
| Operating Frequency | 50/60Hz |
| Operating Temp | -22C (-30F) to +45C (+113F) |
| HID Equivalent | 100W-150W |
| Lumens | 3000L/3375L/3250L |
| Volts | 120V-277V |
| Watts | 25W |

PHYSICAL

| | |
|---------------|--------|
| Lamp Base | Medium |
| Finish | WHITE |
| Housing Color | White |
| ANSI Base | E26 |
| Lamp Type | AP23 |
| MOD Lamps | 2.83 |
| MOL | 5.12 |

ADDITIONAL INFO

| | |
|----------------------------|--------------------------------------|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923131615 |
| Case Cube | 0.877 |
| Case Height | 12.4 |
| Case Length | 12.6 |
| Case Quantity | 24 |
| Case UPC | 10045923131612 |
| Case Weight | 15.8 |
| Case Width | 9.7 |
| EA Cube | 0.0295 |
| EA Height | 5.7 |
| EA Length | 2.99 |
| EA Quantity | 1 |
| EA Weight | 0.63 |
| EA Width | 2.99 |
| Pack Type | Box |
| Web Length | 5.12 |
| Web Width | 2.83 |

COMPLIANCE

| | |
|-----------------|---|
| FCC Compliant | Yes |
| IP Rating | IP64 |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Classified, cULus - Listed |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24 Compliant | No |