



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13182 - 15 Watt LED HID Replacement; ED17; 5000K; Medium Base; White; 120-277 Range Voltage



GENERAL

Company	SATCO
EA Height	6.89
EA Width	2.56
EA Length	2.56
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	LED HID
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 4KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.110-0.050A
Has Camera	No
IOT Enabled	No
Minimum Compartment Size	Length: 5.98 in. Width: 5.98 in. Height: 10.16 in.
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	320
Color Temp	Natural Light
CRI	80+
Operating Frequency	60Hz
Operating Temp	-22F to +149F (-30C to +65C)
HID Equivalent	70W
Lumens	2000L
Volts	120V-277V
Watts	15W

PHYSICAL

Lamp Base	Medium
Finish	WHITE
Housing Color	White
ANSI Base	E26
Lamp Type	ED17
MOD Lamps	2.13
MOL	5.8

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923131820
Case Cube	0.7162
Case Height	8.27
Case Length	13.58
Case Quantity	20
Case UPC	10045923131827
Case Weight	6.03
Case Width	11.02
EA Cube	0.0261
EA Height	6.89
EA Length	2.56
EA Quantity	1
EA Weight	0.26
EA Width	2.56
Pack Type	Box
Web Length	5.8
Web Width	2.13

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No