



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13191 - 40 Watt LED HID Replacement; ED37; 4000K; Extended Mogul Base; Clear; 120-277 Range Voltage



GENERAL

Company	SATCO
EA Height	9.45
EA Width	5.12
EA Length	5.12
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	LED HID
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 4KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Amps	0.330-0.140A
Has Camera	No
IOT Enabled	No
Minimum Compartment Size	Length: 17.83 in. Width: 17.83 in. Height: 13.39 in.
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	320
Color Temp	Cool White
CRI	80+
Operating Frequency	60Hz
Operating Temp	-22F to +149F (-30C to +65C)
HID Equivalent	200W
Lumens	7500L
Volts	120V-277V
Watts	40W

PHYSICAL

Lamp Base	Mogul Extended
Finish	Clear
Housing Color	None
ANSI Base	EX39
Lamp Type	ED37
MOD Lamps	4.7
MOL	10.3

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923131912
Case Cube	1.2746
Case Height	12.6
Case Length	16.14
Case Quantity	6
Case UPC	10045923131919
Case Weight	7.2
Case Width	10.83
EA Cube	0.1434
EA Height	9.45
EA Length	5.12
EA Quantity	1
EA Weight	0.99
EA Width	5.12
Pack Type	Box
Web Length	10.3
Web Width	4.7

COMPLIANCE

DLC ID	S-8517W5
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No